

**What is claimed is:**

1. A signature system presenting a receiver with signature information of a user, comprising:  
5           an input unit inputting the identification information of the user; and  
            an output unit outputting information for generation of the signature information according to the input identification information in a format readable  
10           by a bar cord reader.
2. The system according to claim 1, wherein  
            said output unit encrypts and outputs the identification information.  
15
3. The system according to claim 1, wherein  
            said input unit inputs authentication information, which is significant and repeatedly reproducible by the user, as the identification information.  
20
4. The system according to claim 1, wherein  
            said input unit inputs image data of an image of a seal as the identification information.
- 25   5. The system according to claim 1, wherein

said output unit outputs program information for generation of illegal use prevention information for protection against an illegal use.

5        6.     The system according to claim 5, wherein  
         said     program     information     contains     a  
         one-directional function, and is used in generating blind  
         information of use information using the one-directional  
         function, and generating the illegal use prevention  
10        information containing the blind information.

         7.     The system according to claim 5, wherein  
         said program information contains an encryption  
         key, and is used in generating blind information of use  
15        information using the encryption key, and generating  
         the illegal use prevention information containing the  
         blind information.

         8.     The system according to claim 5, wherein  
20        said program information is prepared such that,  
         after the signature information is generated according  
         to the information for generation of the signature  
         information to present the signature information to the  
         receiver, the program information itself can be removed  
25        from memory.

9. A signature system presenting signature information of a user to a receiver, comprising:

5 a reading unit reading information in a bar code format; and

a generation unit generating the signature information according to the read information.

10 10. The system according to claim 9, wherein said generation unit adds illegal use prevention information for protection against an illegal use to the read information, and generates the signature information.

15 11. The system according to claim 10, wherein said reading unit reads program information for generation of the signature information; and said generation unit generates the illegal use prevention information according to the program information.  
20

12. The system according to claim 10, further comprising:  
25 a timer unit generating date and time information used as the illegal use prevention information.

13. The system according to claim 9, further comprising:

5 a management unit managing blind information of identification information contained in the information in the bar code format; and

10 a comparison unit generating blind information of the identification information from the signature information, and comparing the obtained blind information with blind information managed by said management unit.

14. The system according to claim 13, further comprising

15 an issue unit issuing certification information containing the blind information of the identification information.

15. A signature system, comprising:

20 an input unit through which a user inputs authentication information, which is significant and repeatedly reproducible by the user;

a generation unit generating blind information of the authentication information; and

25 an entry unit entering the blind information in

a device verifying signature information according to the authentication information.

16. The system according to claim 15, wherein  
5       said entry unit enters in the device verifying the signature a one-directional function and an encryption key, which are used to generate the blind information and required to authenticate a user.

10       17. The system according to claim 15, wherein  
          said input unit and said generation unit are provided in a terminal of the user.

15       18. The system according to claim 15, wherein  
          when said user presents the signature information to a receiver for authentication, said user re-enters the authentication information through said input unit; and

20       said generation unit generates the signature information from the re-entered authentication information.

19. The system according to claim 18, further comprising:

25       a generation unit newly generating blind

information from the re-entered authentication information using a one-directional function and an encryption key entered in the device verifying the signature information; and

5           a comparison unit reading blind information entered in the device, and comparing the blind information with the newly generated blind information.

20.   The system according to claim 19, further  
10   comprising

          a deletion unit removing the re-entered authentication information from memory after the newly generated blind information is compared with the blind information entered in the device.

15

21.   The system according to claim 15, wherein  
          said input unit selectively inputs the authentication information from among a plurality of items in an interactive mode with said user.

20

22.   The system according to claim 21, wherein  
          said input unit changes the number of input items of the authentication information depending on a usage of the signature information.

25

23. The system according to claim 15, wherein  
after entering the blind information, said entry  
unit removes the authentication information based on  
which the blind information is generated in order to  
5 avoid an illegal use by others.

24. A computer-readable storage medium storing a  
program used to direct a computer to perform:  
inputting identification information of a user;  
10 generating information for generation of  
signature information of the user according to the input  
identification information; and  
outputting the generated information in a format  
readable by a bar code reader.

15 25. A computer-readable storage medium storing a  
program used to direct a computer to perform:  
reading information in a bar code format; and  
generating signature information of a user based  
20 on the read information.

26. A computer-readable storage medium storing a  
program used to direct a computer to perform:  
inputting authentication information, which is  
25 significant and repeatedly reproducible by a user;

generating blind information of the authentication information; and

entering the blind information in a device verifying signature information according to the authentication information.

27. A signature system presenting a receiver with signature information of a user, comprising:

input means for inputting the identification information of the user; and

output means for outputting information for generation of the signature information according to the input identification information in a format readable by a bar cord reader.

28. A signature system presenting signature information of a user to a receiver, comprising:

reading means for reading information in a bar code format; and

generation means for generating the signature information according to the read information.

29. A signature system, comprising:

input means through which a user inputs authentication information, which is significant and



